DEPARTMENT OF TRANSPORTATION

DIVISION OF ENGINEERING SERVICES OFFICE ENGINEER 1727 30th Street MS-43 P.O. BOX 168041 SACRAMENTO, CA 95816-8041 FAX (916) 227-6214 www.dot.ca.gov/hq/esc/oe



Serious Drought. Help save water!

August 10, 2016

03-ED-49-23.6/24.5 03-0F3104 Project ID 0300000078 ACST-P049(169)

Addendum No. 2

Dear Contractor:

This addendum is being issued to the contract for CONSTRUCTION ON STATE HIGHWAY IN EL DORADO COUNTY NEAR COLOMA FROM 0.1 MILE EAST OF MARSHALL ROAD TO 0.3 MILE EAST OF LOTUS ROAD, to revise the *Notice to Bidders and Special Provisions*.

Submit bids for this work with the understanding and full consideration of this addendum. The revisions declared in this addendum are an essential part of the contract.

Bids for this work will be opened on Wednesday, September 28, 2016.

In the Special Provisions, Section 86-1.01D(b)(3)(i) is added as attached.

To Bid book holders:

Inquiries or questions in regard to this addendum must be communicated as a bidder inquiry and must be made as noted in the *Notice to Bidders* section of the *Notice to Bidders and Special Provisions*.

Submit the Bid book as described in the Electronic Bidding Guide at the Bidders' Exchange website.

http://www.dot.ca.gov/hq/esc/oe/electronic_bidding/electronic_bidding.html

Inform subcontractors and suppliers as necessary.

This addendum, EBS addendum file and attachment are available for the Contractors' download on the Web site:

http://www.dot.ca.gov/hq/esc/oe/project ads addenda/03/03-0F3104

If you are not a *Bid* book holder, but request a book to bid on this project, you must comply with the requirements of this letter before submitting your bid.

Sincerely.

EDWARD ARMIJO Senior, AADD Coordinator

Office Engineer

Division of Engineering Services

Attachment

Replace the table in the RSS for section 86-1.01D(3)(b)(i) with: Nondestructive Testing for Steel Standards and Poles

Weld location	Weld type	Minimum required NDT
Circumferential splices around the perimeter of tubular sections, poles, and arms	CJP groove weld with backing ring	100% UT or RT
Longitudinal seam	CJP or PJP groove weld	Random 25% MT
Longitudinal seam within 6 inches of a circumferential splice	CJP groove weld	100% UT or RT
	CJP groove weld	t≥ 5/16 inch: 100% UT and 100% MT
Welds attaching base plates,	with backing ring and	t< 5/16 inch: 100% MT after root weld
flange plates,	reinforcing fillet	pass and final weld pass
pole plates, or mast arm	External (top) fillet	
plates to poles or arm tubes	weld for socket-type	100% MT
	connections	
Hand holes and other	Fillet and PJP welds	MT full length on random 25% of all
appurtenances		standard and poles

NOTE: t = pole or arm thickness